

2V-Fold Wall is part of the FOLD acoustical tile collection. The acoustic wall tile is designed with a beveled edge adding both dimensionality and modularity to the design. The material and shape provide an effective acoustic solution to your walls.

Simply by changing their orientation on the wall, you can create an unlimited variety of patterns.

2V-Fold Wall

Product Specifications





Material

9mm Polyester (PET) Felt +/- 0.35"



Size

12" (l) x 12" (w) x 3.75" (d)



Weight

1.0 lb



Warranty

3-Year



Flammability

ASTM E84 Class A Certified / CAN/ULC-S102.2



Environmental

Polyester (PET) felt 60% pre-consumer recycled



Color

Choose from one of our standard colors shown below. **See page 4 for additional colors that can be added as accents to your design.**



Slight variations in color should be expected when using this material. We suggest that you request a material sample to verify felt colors.



Acoustics

Wall installation

- Test Method - ASTM E795-16 Type A Mounting - NRC .75

Testing results available upon request at sales@fact.design

**Lead Time**

Ships in four (4) weeks

**Application**

Commercial/Office, Education, Hospitality, Retail

**Pattern**

Non-Directional

**Installation / Maintenance**

The tiles should be installed using a construction-grade adhesive specified by the contractor.

To remove dust or air-borne particulate matter, simply vacuum the tiles or use compressed air. For deeper cleaning of stains, use a clean cloth or sponge with a non-solvent base solution of carpet shampoo always making sure to follow the manufacturer's instructions. Starting from the outside of the stain work in a circular motion towards the center which should avoid spreading the stain. Afterwards, use a clean sponge or cloth with clean warm water to remove excess moisture. Allow to dry, then brush the area gently with a soft brush if needed.

The treatments listed above are intended as general guidance only. FACT design takes no responsibility for any damage that may occur from the execution of the treatment listed above.

**Custom Print**

We can custom-print your tiles with any pattern, image, or color that you can imagine. Tie in your brand, rep your school, or just create something amazing. Get in touch for a quote to custom-print your project.



camira Blazer - Catagory A

Min. Requirements:
Ceilings - 160 sq. ft. per color
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.

camira Blazer Lite - Catagory A

Min. Requirements:
Ceilings - 160 sq. ft. per color
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.

kvadrat Divina 3 - Catagory B

Min. Requirements:
Ceilings - 320 sq. ft. per color
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.

kvadrat Divina Melange 3 - Catagory B

Min. Requirements:
Ceilings - 320 sq. ft. per color
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.

kvadrat Divina MD - Catagory B

Min. Requirements:
Ceilings - 320 sq. ft. per color
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.



metro faux felt - Category A

Min. Requirements:
Ceilings - none
Walls - none
