
Chimes is part of a collection in collaboration with paper artist Merav Peleg. She finds her inspiration through the beauty and details in nature, its textures, in traditional art around the world as well as in fashion.

The surface of this tile is adorned with slender rods or shapes arranged in a way that are reminiscent of chimes. The elements are strategically placed to serve a dual function: aesthetically enhancing the space and providing sound-dampening qualities. When sound waves hit the surface, the tiles' textured patterns and carefully designed shapes help to disperse and absorb the sound, reducing echoes and minimizing noise within the room.

Chimes Wall Tile is comprised of two tiles that can be used together or independently to create an unlimited number of patterns. Simply by changing their orientation on the wall, you can create an unlimited variety of patterns.





	Material 9mm Polyester (PET) Felt +/- 0.35"	
	Size 24" (I) × 24" (w) × +/7" (d)	-
Ō	Weight 3.5 lb	-
	Warranty 3-Year	-
	Flammability ASTM E84 Class A Certified / CAN/ULC-S102.2	-
Ø	Environmental Polyester (PET) felt 60% pre-consumer recycled	-
	Color Choose from one of our standard colors shown below. See page 4 for additional colors that can be added as accents to your design.	-



Slight variations in color should be expected when using this material. We suggest that you request a material sample to verify felt colors.

ം Acoustics

Wall installation

• Test Method - ASTM E795-16 Type E-400 Mounting - NRC ...30

Testing results available upon request at sales@fact.design





Lead Time

Ships in four (4) weeks

Application

Commercial/Office, Education, Hospitality, Retail



Pattern Non-Directional



Installation / Maintenance

The tiles should be installed using a construction- grade adhesive specified by the contractor.

To remove dust or air-born particulate matter, simply vacuum the tiles or use compressed air. For deeper cleaning of stains, use a clean cloth or sponge with a non-solvent base solution of carpet shampoo always making sure to follow the manufacturer's instructions. Starting from the outside of the stain work in a circular motion towards the center which should avoid spreading the stain. Afterwards, use a clean sponge or cloth with clean warm water to remove excess moisture. Allow to dry, then brush the area gently with a soft brush if needed.

The treatments listed above are intended as general guidance only. FACT design takes no responsibility for any damage that may occur from the execution of the treatment listed above.

\oplus

Custom Print

We can custom-print your tiles with any pattern, image, or color that you can imagine. Tie in your brand, rep your school, or just create something amazing. Get in touch for a quote to custom-print your project.



camira Blazer - Catagory A

Min. Requirements: Ceilings - 160 sq. ft. per color Walls - 40 sq. ft. per color

If your project requires less, please reach out to your local rep to discuss the project.

camira Blazer Lite - Catagory A

Min. Requirements: Ceilings - 160 sq. ft. per color Walls - 40 sq. ft. per color

If your project requires less, please reach out to your local rep to discuss the project.

kvadrat Divina 3 - Catagory B

Min. Requirements: Ceilings - 320 sq. ft. per color Walls - 40 sq. ft. per color

If your project requires less, please reach out to your local rep to discuss the project.

kvadrat Divina Melange 3 - Catagory B

Min. Requirements: Ceilings - 320 sq. ft. per color Walls - 40 sq. ft. per color

If your project requires less, please reach out to your local rep to discuss the project.

kvadrat Divina MD - Catagory B

Min. Requirements: Ceilings – 320 sq. ft. per color Walls – 40 sq. ft. per color

If your project requires less, please reach out to your local rep to discuss the project.



metro faux felt - Category A

Min. Requirements: Ceilings - none Walls - none

