

**Flow** is a collaboration with Peter Dahmen, both designer and paper artist.

The concept behind flow was to create a grid that restricts the viewer's gaze by dropping cuboids of felt from each tile in such a way that only a partial aspect of the colored background's surface is visible. Viewing the ceiling from different angles changes the perceived colorfulness. It is impossible to grasp the objects in their entirety at a single glance. Only by changing the angle of view can the colorfulness of the tiles gradually be fully grasped. As soon as the viewer moves, the impression is created that the tiles are changing or transforming.

Flow was designed to create an interaction between the person and their environment.

Optimal ceiling heights for FLOW is between 9'-0" - 10'-0". If your project requires a different layout or ceiling heights, please let us know and we will consult with the designer, Peter Dahmen, to help create a custom FLOW for your project.

Installation types:

Drop the tiles into any 9/16" or 15/16" tee-grid.

Concealed tile install - tiles fit neatly together edge-to-edge, to conceal the actual grid.





**Material**

9mm Polyester (PET) Felt +/- 0.35"



**Size**

23.75" (l) x 23.75" (w) x 4.2"/3.3"/2.4"(d)

note: 6" clearance required above grid. In areas where you do not have this clearance, the flat tile is required.



**Weight**

3.30 lb



**Warranty**

3-Year



**Flammability**

ASTM E84 Class A Certified / CAN/ULC-S102.2



**Environmental**

Polyester (PET) felt 60% pre-consumer recycled



**Color**

Choose from one of our standard colors shown below. See page 4 for insert color options.



Slight variations in color should be expected when using this material. We suggest that you request a material sample to verify felt colors.



**Acoustics**

Cloud installation

- Test Method - ASTM E795-16 Type J Mounting closed tile - NRC 1.25
- Test Method - ASTM E795-16 Type J Mounting open tile - NRC .9

Closed/open plenum installation

- Test Method - ASTM E795-16 Type E-400 Mounting closed tile - NRC 1.0
- Test Method - ASTM E795-16 Type E-400 Mounting open tile - NRC .9

Testing results available upon request at sales@fact.design



### Lead Time

Ships in four (4 - 6) weeks



### Application

Commercial/Office, Education, Hospitality, Retail



### Pattern

Layout to be developed with specifier



### Installation / Maintenance

Configure each tile according to the illustrations below. Insert the finished tiles into the tee grid.

To remove dust or air-born particulate matter, simply vacuum the tiles or use compressed air. For deeper cleaning of stains, use a clean cloth or sponge with a non-solvent base solution of carpet shampoo always making sure to follow the manufacturer's instructions. Starting from the outside of the stain work in a circular motion towards the center which should avoid spreading the stain. Afterwards, use a clean sponge or cloth with clean warm water to remove excess moisture. Allow to dry, then brush the area gently with a soft brush if needed.

The treatments listed above are intended as general guidance only. FACT design takes no responsibility for any damage that may occur from the execution of the treatment listed above.



## **camira Blazer - Catagory A**

Min. Requirements:  
Ceilings - 160 sq. ft. per color  
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.

---

## **camira Blazer Lite - Catagory A**

Min. Requirements:  
Ceilings - 160 sq. ft. per color  
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.

---

## **kvadrat Divina 3 - Catagory B**

Min. Requirements:  
Ceilings - 320 sq. ft. per color  
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.

---

## **kvadrat Divina Melange 3 - Catagory B**

Min. Requirements:  
Ceilings - 320 sq. ft. per color  
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.

---

## **kvadrat Divina MD - Catagory B**

Min. Requirements:  
Ceilings - 320 sq. ft. per color  
Walls - 40 sq. ft. per color

If your project requires less, please reach out to your **local rep** to discuss the project.



**metro faux felt - Category A**

Min. Requirements:  
Ceilings - none  
Walls - none

---